

Datavideo Product Compare

<https://datavideo.com/fr/>

Numéro de modèle	PTR-15-SKA
Product	PTR-15 with SKAARHOJ
Video Interface	HDMI 2.0 x 1 12G-SDI x 1 3G-SDI x 1
Video Output	2160p 60/59.94/50 2160p 30/29.97/25 1080p 60/59.94/50 1080p 30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50
Control Unit	
Genlock	YES
Timecode	YES
Panning / Tilting Range	Pan: 340° Tilt: ±45°
Panning / Tilting Speed	Pan: 0.12~15° /Sec Tilt: 0.06~10° /Sec
Preset	Pan/Tilt position 199
Control Distance	1,200M by RS422 100M by DVIP
Control Protocal	Sony VISCA DVIP

Control Input	RS-422 DVIP
Maximum Load	4 KG Max
Control Output	RS-232 RS-422 IP Control BX-Lens LanC
Power Requirement	DC 14V~ 20V, 90W
Power Supply	DC 24/12V, 36W Max
Operating Temp. Range	0~40 C°
Operating Humidity Range	10~80%
Storage Temp. Range	-10~60C°
Storage Humidity Range	5~80%
Weight	3.7 kg
Dimension (LxWxH)	241 x 191 x 300 mm
Optional accessories	PZA KIT PZA-BPX KIT PZA-RKX KIT PZA-RKX-S KIT WM-10 WM-11 CM-10

What's in the Box	SKAAHOJ PTZ Pro V2B Controller PTR-15 Main Unit x 1 DC 19V power adaptor x 1 AC cord x 1 IR remote control x 1 DC with lock to D-Tap cable x 1 HDMI cable x 1 SDI cable x 1 Remote cable (2.5mm phone-jack to mini-din 8pin) x 1 1/4" screw x 2 1/4" to 3/8" screw adaptor x 1
-------------------	--