

Datavideo Product Compare

<https://datavideo.com/fr/>

Numéro de modèle	SE-700
Product	Mélangeur HD - 4 entrées
Video Standard	HD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
Video Processing	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB: 4:4:4
Input Routable / Crosspoint	All 4, repeatable
Video Input	2xHD-SDI 2xHDMI
Mix HD & SD Source	----
Computer Graphic Interface	2 via HDMI
Video Output	2x HD-SDI & 1x HDMI assignable: PGM(w/DSK),PGM Clean, PVW (w/o DSK), multi-view, Input 1-4 PVW+DSK1, Still Freeze
Down-converted Output	----

Built-in Multi-view Monitoring Out	HDMI
Analogue Audio Input	2x Balanced XLR
Analogue Audio Output	----
Digital Embedded Audio Support	embedded 2-CH audio output from XLR input
Audio Delay Calibration	----
A+V Switching	----
Chromakey	1
Title Creator	----
USK	2x USK supports M/E Keyer & PIP
DSK	1
Picture in Picture	1
Logo Insertion	----
Still Store	999+
Effects	FTB, Cut, 32 Wipe with border
Transition Preview	Full transitions preview
Sync / Reference In/Out	Built-in Genlock (internal)
Tally Output	1x D-sub 15pin, dual color

PC Remote Control	Via Ethernet (free Window software)
Camera Control	
Built-in Audio Mixer	----
Storage	
Recording File System	
Recording File Format	
Video Encode	
Audio Encode	
Streaming Protocol	
Firmware Update	
Special Features	12 Macro Memory Preset Stinger transition
Chassis	Unibody
Dimension (LxWxH)	433 x 313 x 81 mm
Weight	2.9 kg
Power	DC 12V 23W
Operating Temp. Range	0~40 °C
What's in the Box	1 x SE-700 product 1 x AD Switch DC 12V with AC Cord