

Video Decoder

**SDI IP Video Decoder****NVD-35 MARK II**

|                               |   |
|-------------------------------|---|
| Audio/Video Input             | <p>Stream Input</p> <ul style="list-style-type: none"> <li>· RTSP over UDP (Unicast / Multicast)</li> <li>· RTSP over TCP</li> <li>· RTSP over HTTP</li> <li>· SRT (Secure Reliable Transport) caller</li> <li>· MPEG-TS over UDP</li> <li>· RTMP Pull</li> <li>· RTMP Push (Internal Server)</li> <li>· UDP raw (Unicast/Multicast)</li> <li>· HLS over HTTP</li> <li>· MPEG-TS over TCP Pull</li> <li>· Video sharing websites</li> </ul> |
| Audio Output                  | <p>2 x RCA(L/R)<br/>SDI embedded audio</p>  |
| Video Output                  | <p>Composite (analogue)<br/>SDI (digital)</p>   |
| Network Feature               | <p>1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP</p>  |
| Supported Video Resolution    | <p>1080p 60/59.94/30/29.97/25/24<br/>1080i 60/59.94/50<br/>720p 60/59.94/50<br/>576i 50 (PAL)<br/>480i 60 (NTSC)</p>  |
| Supported Decoding Resolution | <p>Up to 1080p60/50</p>   |
| Control                       | <p>Web browser UI for configuration and control.<br/>TCP/IP Socket commands</p>   |
| Update                        | <p>Automatic firmware upgrade</p>   |
| Power                         | <p>Input AC 100~240V Switching Adaptor<br/>Output DC 12V / 1A</p>   |
| Environmental Conditions      | <p>Operating temperature: 0~40°C, Storage temperature: -10~60°C</p>   |
| Dimension (LxWxH)             | <p>220 x 143 x 47 mm</p>  |
| Weight                        | <p>1 kg</p>   |
| Power                         | <p>DC 12V, 1A</p>   |
| What's in the Box             | <p>1 x NVD-35 MARK II product<br/>1 x AD Switch DC 12V<br/>1 x Remote Control</p>   |