

Video Decoder

SDI IP Video Decoder**NVD-35 MARK II**

| | |
|-------------------------------|--|
| Audio/Video Input | Stream Input <ul style="list-style-type: none"> · RTSP over UDP (Unicast / Multicast) · RTSP over TCP · RTSP over HTTP · SRT (Secure Reliable Transport) caller · MPEG-TS over UDP · RTMP Pull · RTMP Push (Internal Server) · UDP raw (Unicast/Multicast) · HLS over HTTP · MPEG-TS over TCP Pull · Video sharing websites |
| Audio Output | 2 x RCA(L/R) SDI embedded audio |
| Video Output | Composite (analogue) SDI (digital) |
| Network Feature | 1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP |
| Supported Video Resolution | 1080p 60/59.94/30/29.97/25/24 1080i 60/59.94/50 720p 60/59.94/50 576i 50 (PAL) 480i 60 (NTSC) |
| Supported Decoding Resolution | Up to 1080p60/50 |
| Control | Web browser UI for configuration and control. TCP/IP Socket commands |
| Update | Automatic firmware upgrade |
| Power | Input AC 100~240V Switching Adaptor Output DC 12V / 1A |
| Environmental Conditions | Operating temperature: 0~40°C, Storage temperature: -10~60°C |
| Dimension (LxWxH) | 220 x 143 x 47 mm |
| Weight | 1 kg |
| Power | DC 12V, 1A |
| What's in the Box | 1 x NVD-35 MARK II product 1 x AD Switch DC 12V 1 x Remote Control |