

Robotic Pan Tilt Head

Robotic Pan Tilt Head**PTR-10 MARK II**

| | |
|--------------------------|---------------------------------------------------------------------------------------------------------|
| Video Interface | HDMI x 1 SDI x 1 |
| Video Output | 2160p 29.97/25 1080p 59.94/50 1080i 59.94/50 720p 59.94/50 |
| Control Unit | RMC-180 RMC-300A RMC-300C ShowCast 100 VISCA Protocol Controller IP Control IR remote |
| Genlock | --- |
| Timecode | --- |
| Panning / Tilting Range | Pan: 340° Tilt: ±45° |
| Panning / Tilting Speed | Pan: 0.12~15° /Sec Tilt: 0.06~10° /Sec |
| Preset | Pan/Tilt position 50 |
| Control Distance | 1,200M by RS422 100M by DVIP |
| Control Protocol | Sony VISCA DVIP |
| Control Input | RS-422 DVIP |
| Maximum Load | 4 KG Max |
| Control Output | RS-232 RS-422 BX-Lens LanC |
| Power Requirement | DC 12V~ 18V, 3A (Without Camera) DC 12V~ 18V, 5A (With Camera) |
| Power Supply | DC 12/10/8.4/7.4V, 24W Max |
| Operating Temp. Range | 0~40 C° |
| Operating Humidity Range | 10~80% |
| Storage Temp. Range | -10~60C° |
| Storage Humidity Range | 5~80% |
| Weight | 3.4 kg |
| Dimension (LxWxH) | 230 x 190 x 300 mm |

| | |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Optional accessories | ZEK-1 WM-10 WM-11 CM-10 |
| What's in the Box | PTR-10 Mark II Main Unit x 1 DC 12V power adaptor x 1 AC cord x 1 IR remote control x 1 DC with lock to D-Tap cable x 1 HDMI cable x 1 SDI cable x 1 Remote cable (2.5mm phone-jack to mini-din 8pin) x 1 1/4" screw x 2 1/4" to 3/8" screw adaptor x 1 |