

LCD Monitors

4K 17" ScopeView Production Monitor**TLM-170KM**

| | |
|-----------------------------|---|
| Screen | 17.3" LED Backlit |
| Chassis | Pull-Out |
| Resolution | 3840 × 2160 |
| Viewing Angle | (H) +89/-89° (V) +89/-89° |
| Luminance/Contrast | 300cd/m ² 1000:1 |
| Video Inputs | 1 x 12G SDI 2 x HDMI (2.0) |
| Loop Through | 1 x 12G SDI 1 x HDMI (2.0) |
| Supported Input Resolutions | SDI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 4096x2160Psf (23.98/24/25/29.97/30) 3840x2160Psf (23.98/24/25/29.97/30) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1920x1080Psf (23.98/24/25/29.97/30) 1280×720p (23.98/24/25/29.97/30/50/59.94/60) 525i, 625i HDMI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1280×720p (23.98/24/25/29.97/30/50/59.94/60) 720 x480i (NTSC), 720 x576i (PAL) 640 x800, 800 x600, 1024 x768, 1280 x800 |
| Aspect Ratio | 16:9, 4:3 |
| Aspect Marker | YES |
| Safty Marker | YES |
| Tally LED | Live (Red) Cued (Green) |
| Audio In/Out | Input: Embedded Audio (48KHz sampling) Output: Analog stereo (Phone Jack) Speaker x 2 (3W) |

| | |
|-----------------------|--|
| Special Features | <p>waveform, vector scope, Focus Peaking, False Color, Exposure (Zebras), Histogram, HDR / SDR, Time Code, Audio Vector, Camera Log, Gamma, Marker, Pixel to Pixel, Zoom, H/V Delay, DSLR, Freeze, Image Flip, Check Field, Level Meter, Color Bar, Color Calibration.</p> |
| Dimension (WxHxD) | 403 x 305 x 37 mm |
| Weight | 5.2kg |
| Operating Temp. Range | 0~40 °C |
| Power | DC 12V, 40.1W |
| What's in the Box | <p>1 x TLM-170KM product 1 x AD Switch DC 12V 4 x Screw ϕ4.0*6m/m 8 x Screw ϕ3.0*6m/m 8 x Screw M5 x 10mm 5 x Cable tie</p> |