

# Datavideo Product Compare

<https://datavideo.com/global/>

|                                      |                                                                                                                                    |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Model Number                         | <b>PD-6A</b>                                                                                                                       |
| Product                              | <b>Power Center</b>                                                                                                                |
| AC Input                             | 100~240 VAC (50Hz or 60Hz)<br>(500W: 110V-120V/5A~220V-240V/2.6A)<br>AC input outlet: One AC input with Power Switch               |
| DC Backup Input                      | ----                                                                                                                               |
| DC Output                            | 8 DC Outputs (4 pin female XLR) 60W: 48V (1.25A)<br>PIN 1: GND<br>PIN 2: DC OUT<br>PIN 3/4: N/C                                    |
| Max. Power Rating                    | 500W                                                                                                                               |
| DC Overload                          | 105%~150% rated output power<br>Protection type: Recovery automatically after fault condition is removed                           |
| AC Overload                          | non-recovery fuse on the AC input outlet                                                                                           |
| LED Indicator                        | LED indicator for DC output: Green on operation<br>Note: If DC out is shorted or overloaded, the LED indicator will be turned off. |
| Power Source Input Select<br>AUTO/AC | ----                                                                                                                               |
| Dimension (LxWxH)                    | 440 x 235 x 46 mm                                                                                                                  |
| Weight                               | 5.2 kg                                                                                                                             |
| Power                                | AC 100-240 VAC                                                                                                                     |

|                             |                                  |
|-----------------------------|----------------------------------|
| Operating<br>Temp.<br>Range | 0~40 °C                          |
| What's in<br>the Box        | 1 x PD-6A Product<br>1 x AC Cord |