

HDBaseT

**三路HDBaseT 影音接收器****HBT-30**

|                |  |
|----------------|--|
| 影像/聲音輸入        | HDBaseT (RJ-45) x 3  |
| 影像/聲音輸出        | HDMI 2.0 x 3   |
| 影像格式           | 3840x2160p: 60/59.94/50/30/29.97/25/24/23.98<br>1080p: 60/59.94/50/30/29.97/25/24/23.98<br>1080i: 60/59.94/50<br>720p: 60/59.94/50<br>525i: 59.94 NTSC<br>625i: 50 PAL |
| 影像處理           | 4K60 4:4:4, 8bit<br>4K60 4:2:2 10bit<br>4K60 4:2:0 10bit   |
| 影像帶寬           | Single-link 594MHz [18Gbps]  |
| DVIP           | RJ-45 x1(input)  |
| RS-422/ RS-232 | RJ-45 x 3 (RS-232/RS-422)  |
| 電源             | DC IN: DC 56V  |
| PoE Output     | 65W per channel  |
| HDBaseT傳輸距離    | 1080p@60 up to 100M by CAT. 6A cable<br>4K@60 up to 100M by CAT. 6A cable  |
| HDMI 規範        | HDMI Deep Color & 4K@60  |
| HDCP 規範        | HDCP 2.2/1.4 (Bypass)  |
| 聲音格式           | Surround Sound [up to 7.1 Channel) or Stereo Digital Audio   |
| 尺寸             | 440 x 125 x 44.5 mm  |
| 重量             | 1.8Kg  |
| 操作溫度           | 0~40 °C  |
| 附件             | 1 x HBT-30 main unit<br>1 x AC cord<br>1 x DC 56V power adaptor  |