

攝影機

HD/SD PTZ Video Camera with HBT-11 HDBaseT Receiver

PTC-150TL-11

影像格式	1080p 59.94/50/29.97/25 1080i 59.94/50 720p 59.94/50 480i, 576i (on CVBS)
感光元件	1/2.8" type progressive scan CMOS sensor
有效畫素	2.14 Mega pixels
信噪比	50dB
最小明亮度	Color : 0.4 lx B/W : 0.03 lx (F1.6, 1/30 sec, 50IRE, Gain: High)
電子快門	1/25~1/1250 sec (50/25Hz) 1/30~1/1500 sec (59.94/29.97Hz)
鏡頭倍率	30x Optical Zoom
Gamma	Off / Normal / Standard Mode 1-4
光圈設定	Auto / Manual
數位降噪	Yes
選單使用語言	English
白平衡	AWB, MWB, One push WB, Outdoor, Indoor, Fluorescent
ACG/增益控制	Auto / Manual Max. Gain Limit
鏡頭翻轉	Yes
對焦模式	Auto / Manual
水平/垂直範圍	Pan: 270° , Tilt: +90° to -20°
水平/垂直移動速度	Manual: 1~150°/Sec Swing: 1~150°/Sec
預設點	50 Position
焦距	f=4.3 mm (WIDE) to 129 mm (TELE) F1.6 to F4.7
視角	Approx. 63.7° (WIDE END) / 2.3° (TELE END)
圖像補償	Day & Night function
影像輸出	HDMI (V1.3) x 1 3G-SDI x 1 CVBS x 1 HDBaseT x 1 to PTC-150T Receiver Box
聲音輸入	----
Tally燈	Dual color (Red, Green)
濾片或廣角鏡	M52.0 x 0.75 Thread with UV Protection
Protocol	VISCA, DVIP

遠端控制端子	RS-422: Transmit up to 1000m HDBaseT (RJ-45)/ DVIP on Receiver Box: Transmit up to 100m
影像壓縮格式	----
聲音壓縮格式	----
聲音比特率	----
HD IP Interface	----
串流協議	----
第一串流直播解析度	----
第二串流直播解析度	----
影像比特率	----
影像比特率模式	----
編碼 Frame rate	----
POE	----
韌體更新	USB
IR控制	Yes
攝影機控制器	HS-1500T/HS-1600T series/RMC-180 series/RMC-300 series
腳架用螺絲尺寸	1/4-20 UNC
可用附件	WM-1/ WM-10/ WM-11
顏色	Black/White
尺寸	173 x 189 x 219 mm
重量	2.7 kg
操作溫度	0~40 °C
電源	DC 12V 29W
附件	1 x PTC-150T/TW Unit 1 x HBT-11 Receiver Box 1 x IR remote controller 1 x Ceiling mount bracket-A 1 x Ceiling mount bracket-B 6 x Ceiling mount bracket screw M3*4mm 1 x DC 12V Power Adaptor 1 x DC 48V Power Adaptor 2 x Power Cord 1 x A tightrope 1 x Phoenix connector to RJ-45