

導播機

HD 6通道導播機**SE-1200MU**

| | |
|----------|--|
| 影像系統 | HD |
| 影像格式 | 1080i 50/59.94/60Hz 720p 50/59.94/60Hz |
| 影像處理 | SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4 |
| 輸入設定 | All 6, repeatable |
| 影像輸入 | 4x HD-SDI 2x HDMI (RGB/YUV, 1080i/1080p/720p) |
| 相容HD/SD | ---- |
| 電腦連結 | 2 via HDMI |
| 影像輸出 | 2x HD-SDI 2x HDMI assignable: PGM(w/DSK 1&2), PGM(w/DSK 1), PGM Clean, PVW(w/o DSK), multi-view, Input 1-6 |
| 下轉輸出 | ---- |
| 多分割監看 | HDMI & SDI assignable, Ethernet (MJPEG) |
| 聲音輸入 | 2x Balanced XLR |
| 聲音輸出 | ---- |
| 支持聲音軌數 | Input 2 channels, Output 2 channels |
| 聲音延遲 | ---- |
| 影音像同步切換 | Yes |
| 影像去背 | 2 |
| 字幕機 | ---- |
| USK | 2x Keyer support Chromakey/ Linear/ Luma Key |
| DSK | 2x DSK support Lumakey/ Linear key (Key / Fill) |
| 子母畫面 | 1 |
| LOGO顯示 | ---- |
| 靜態圖片儲存 | 500 |
| 特效 | FTB, Cut, 32 Wipe with border |
| 過場預覽 | Full transitions preview |
| 同步訊號輸入/出 | Built-in Genlock (internal) |
| Tally輸出 | 1x D-sub 15pin, dual color |
| 電腦控制 | Ethernet (free Window software) RS-422/ RS-232 |
| 混音器 | ---- |

| | |
|------|---|
| 特別功能 | Motion JPEG Multi-view streaming (120 memory preset, BGD Transition on/off option) Free Virtual Set and Stinger transition included |
| 外型 | 1RU rack-mount mainframe |
| 尺寸 | 440 x 215 x 49 mm |
| 重量 | 1.5 kg |
| 電源 | DC 12V, 19W |
| 操作溫度 | 0~40 °C |
| 附件 | 1 x SE-1200MU product 1 x AD Switch DC 12V 1 x DB9P TO DB9P Cable 2 x 1U Rack Mount Ear 6 x M4 Screws for Rack Mount Ear |