

液晶監視螢幕

4K 17吋向量示波液晶監視螢幕-1U折疊式**TLM-170KM**

面板	17.3" LED Backlit
外觀	Pull-Out
解析度	3840 × 2160
可視角度	(H) +89/-89° (V) +89/-89°
亮度/對比	300cd/m ² 1000:1
影像輸入	1 x 12G SDI 2 x HDMI (2.0)
環通輸出	1 x 12G SDI 1 x HDMI (2.0)
支援影像格式	SDI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 4096x2160Psf (23.98/24/25/29.97/30) 3840x2160Psf (23.98/24/25/29.97/30) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1920x1080Psf (23.98/24/25/29.97/30) 1280×720p (23.98/24/25/29.97/30/50/59.94/60) 525i, 625i HDMI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1280×720p (23.98/24/25/29.97/30/50/59.94/60) 720 x480i (NTSC), 720 x576i (PAL) 640 x800, 800 x600, 1024 x768, 1280 x800
長寬比顯示模式	16:9, 4:3
參考線/畫面檢閱器	YES
安全框	YES
Tally模式	Live (Red) Cued (Green)
聲音輸入/輸出	Input: Embedded Audio (48KHz sampling) Output: Analog stereo (Phone Jack) Speaker x 2 (3W)

特別功能	waveform, vector scope, Focus Peaking, False Color, Exposure (Zebras), Histogram, HDR / SDR, Time Code, Audio Vector, Camera Log, Gamma, Marker, Pixel to Pixel, Zoom, H/V Delay, DSLR, Freeze, Image Flip, Check Field, Level Meter, Color Bar, Color Calibration.
尺寸	403 x 305 x 37 mm
重量	5.2kg
操作溫度	0~40 °C
電源	DC 12V, 40.1W
附件	1 x TLM-170KM product 1 x AD Switch DC 12V 4 x Screw $\phi 4.0 \times 6$ m/m 8 x Screw $\phi 3.0 \times 6$ m/m 8 x Screw M5 x 10mm 5 x Cable tie