

Datavideo Product Compare

<https://datavideo.com/hk/>

型號	HS-1400
產品	HD 5 通道 手提式移動錄播導播室
影像系統	HD
影像格式	Input: HDMI 3840x2160p: 60/59.94/50/30/29.97/25/24 (HDMI Input 1/2) 1080p: 60/59.94/50/30/29.97/25/24 1080i: 60/59.94/50 720p: 60/59.94/50 Output: 1080p: 60/59.94/50/30/29.97/25/24 1080i: 60/59.94/50
輸入格式設定	All 8, repeatable
影像輸入	4 x HDMI (2 x 2.0 + 2 x 1.4a) 4 x 3G-SDI selectable NDI HX2 and media input selectable
電腦輸入	4 via HDMI
下變換轉換器	-----
影像輸出	2x HDMI PGM 1x HDMI for PGM (AUX assignable) 1x SDI for PGM (AUX assignable) 1x USB Type-C (UVC)
聲音輸入	2x Balanced XLR 1x Stereo RCA (L/R) De-embedded Digital Audio

聲音輸出	1x Stereo headphone
聲音嵌入	Input 2 channels, Output 2 channels
聲音延遲	Up to 1000 ms
聲音同步切換	Yes
USK	2x USK support Chromakey and Lumakey
DSK	1
子母畫面	2
LOGO	2
字幕機	---
混音機	Yes
監看螢幕	17.3" HD TFT LED backlit, 1920x1080 pix
通話系統	----
Streaming	
串流影片編碼	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 20Mbps
串流聲音編碼	AAC 2CH, Sample rate: 48KHz
串流協議	RTSP RTMP SRT NDI Hx2
串流控制	Web browser UI for configuration and control Socket commands
錄製檔案系統	FAT32, exFAT, NTFS
錄製檔案格式	MP4, TS, FLV
錄製設定控制	Web UI for system configuration and control
Others	

特別功能	Support Media Player via USB, SD Card Support NDI HX2 input
尺寸	455 x 370 x 134 mm
重量	7.3 kg, Reinforce Plastic Case
电源	DC 12V, 5A
操作溫度	0~40 °C
附件	1 x HS-1400 Unit 1 x AD Switch DC 12V with AC Cord