

# Datavideo Product Compare

<https://datavideo.com/hk/>

|                  |                                                                                                                  |
|------------------|------------------------------------------------------------------------------------------------------------------|
| 型號               | <b>ITC-100</b>                                                                                                   |
| 產品               | <b>導播通話系統</b>                                                                                                    |
| Tally 接口         | 2 x 15 Pin DSub Sockets for Tally A and B                                                                        |
| 耳機麥克風<br>接口      | 3.5 mm Stereo Jack Socket for Headphone / Microphone combination<br>Headset Impedance 8-600 Ohms 100 mW (min)    |
| 耳機接口             | ¼" (6.3mm) Stereo Headphone Socket<br>Headset Impedance 8-600 Ohms 100 mW (min)                                  |
| 燈光接口<br>(DC 12V) | 3 PIN XLR Connector<br>PIN 2: 12V<br>PIN 3: GND<br>Light Power Consumption: 12 V / 100 mA (MAX.)                 |
| 麥克風接口            | 3 PIN XLR / ¼" (6.3mm) Jack Microphone Socket<br>Switchable Condenser / Dynamic Input<br>Microphone Level -67 dB |
| 頻率響應             | 550-3.6 kHz, <+/- 3dB                                                                                            |
| 總諧波失真(THD)       | < 3%                                                                                                             |
| 訊號雜訊<br>比(S/N)   | > 50dB                                                                                                           |
| 內建麥克風            | 70mm x 30mm 32 Ohm 3 Watts                                                                                       |
| 操作範圍             | Up to 200 meters between base station and slave                                                                  |
| 操作溫度             | 0~40 °C                                                                                                          |
| 尺寸               | 482 x 127 x 46 mm                                                                                                |
| 重量               | 1.9 kg                                                                                                           |
| 電源               | DC 12V, 8W                                                                                                       |

附件

- 1 x ITC-100 Base Unit
- 4 x ITC-100SL Belt Pack
- 4 x ITC-100SL Carry Case
- 4 x Cable 5pin 20cm XLR to XLR
- 4 x 3.5mm Jack to 3.5mm Jack Cable
- 4 x Headset with microphone
- 4 x Tally LED Indicator
- 1 x XLR Gooseneck Microphone
- 1 x XLR Gooseneck Light
- 1 x 12V 1A Power Supply Unit