

Datavideo Product Compare

<https://datavideo.com/hk/>

型號	PTC-285T
產品	4K 12x HDBaseT自動追蹤雲台攝影機
影像格式	HDMI/HDBaseT: 2160p60/59.94/50/30/29.97/25 1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50 *2160p60/59.94/50 YUV 4:2:2 SDI: 1080p 60/59.94/50/30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50
感光元件	Sony 1/2.8" CMOS
有效畫素	8.51Mega Pixels
信噪比	≥55dB
最小明亮度	0.5 Lux @ (F1.8, AGC ON)
電子快門	1/30s ~ 1/10000s
鏡頭倍率	12x Optical Zoom, 16x Digital Zoom
有效變焦倍率	12x
Gamma	N/A
光圈設定	Auto / Manual
數位降噪	3D
選單使用語言	English/Simplified Chinese/Traditional Chinese

白平衡	Auto, Indoor, Outdoor, OnePush, Manual, VAR
ACG/增益控制	Yes
HDR/WDR	N/A
鏡頭翻轉	Yes
對焦模式	Auto/Manual
水平/垂直範圍	Pan: 300° Tilt: +90° to -15°
水平/垂直移動速度	Pan: 0.876°/s~43°/s Tilt: 0.693°/s ~21.32°/s
預設點	255
焦距	12x, f = 4.4mm ~ 52.8mm, F1.8 ~ F2.6
視角	80°
圖像補償	Back light compensation
影像輸出	HDMI 2.0 x1 3G-SDI x1 HDBaseT (PoE) x 1 Cable Type: Cat6A Shielded
聲音輸入	3.5 mm x1 (mic in/line in) switch from Web UI
Tally燈	Yes
濾片或廣角鏡	N/A
Protocol	Pelco-D, Pelco-P, VISCA, VISCA over IP, DVIP, ONVIF
遠端控制端子	IR Web GUI RS-422/RS-232 DVIP HDBaseT(RJ-45)/Serial control on Receiver Box: Transmit up to 100m
影像壓縮格式	H.264/H.265/MJPEG

聲音壓縮格式	AAC, G711
聲音比特率	96Kbps, 128Kbps, 256Kbps
HD IP Interface	----
串流協議	RTSP, RTMP(S), ONVIF, Multicast, SRT
第一串流直播解析度	3840x2160 1920x1080 1280x720 1024x576 960x540 640x480 640x360
第二串流直播解析度	720x480 640x360 480x270 320x240
影像比特率	32Kbps ~ 50Mbps (Single Stream)
影像比特率模式	VBR, CBR
編碼 Frame rate	50Hz: 1-50fps 60Hz: 1-60fps
POE	IEEE 802.3at
韌體更新	Via Web UI or USB 2.0
IR控制	Yes
攝影機控制器	HS-1650T/HS-1600T Mark II/RMC-2P/RMC-180 series/RMC-300 series/PTZ View Assist APP
腳架用螺絲尺寸	1/4-20 UNC
可用附件	WM-1/ WM-10/ WM-11
顏色	Black/White
尺寸	184(W) x 228.5(H) x 194(D)
重量	2.7 kg

操作溫度	0~40 °C
電源	DC 12V 22W
附件	1 x PTC-285T product 1 x RMC-1AT IR remote controller 1 x Ceiling mount bracket -B 6 x Ceiling mount bracket screw M3*4mm 1 x DC 12V Power Adaptor 1 x Safety cable