

# Datavideo Product Compare

<https://datavideo.com/hk/>

|             |                                                                                                                  |
|-------------|------------------------------------------------------------------------------------------------------------------|
| 型號          | <b>SEB-1200</b>                                                                                                  |
| 產品          | <b>SE-1200MU 6 Input Switcher + RMC-260 Controller Bundle</b>                                                    |
| 影像系統        | HD                                                                                                               |
| 影像格式        | 1080i 50/59.94/60Hz<br>720p 50/59.94/60Hz                                                                        |
| 影像處理        | SDI: 4:2:2<br>HDMI: YUV 4:2:2 10 bit, RGB 4:4:4                                                                  |
| 輸入設定        | All 6, repeatable                                                                                                |
| 影像輸入        | 4x HD-SDI<br>2x HDMI (RGB/YUV, 1080i/1080p/720p)                                                                 |
| 相容HD/SD     | ----                                                                                                             |
| 電腦連結        | 2 via HDMI                                                                                                       |
| 影像輸出        | 2x HD-SDI<br>2x HDMI assignable:<br>PGM(w/DSK 1&2), PGM(w/DSK 1), PGM Clean, PVW(w/o DSK), multi-view, Input 1-6 |
| 下轉輸出        | ----                                                                                                             |
| 多分割監看       | HDMI & SDI assignable, Ethernet (MJPEG)                                                                          |
| 聲音輸入        | 2x Balanced XLR                                                                                                  |
| 聲音輸出        | ----                                                                                                             |
| 支持聲音軌數      | Input 2 channels, Output 2 channels                                                                              |
| 聲音延遲        | ----                                                                                                             |
| 影音像同步<br>切換 | Yes                                                                                                              |

|          |                                                                                                                                           |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------|
| 影像去背     | 2                                                                                                                                         |
| 字幕機      | ----                                                                                                                                      |
| USK      | 2x Keyer support Chromakey/ Linear/ Luma Key                                                                                              |
| DSK      | 2x DSK support Lumakey/ Linear key (Key / Fill)                                                                                           |
| 子母畫面     | 1                                                                                                                                         |
| LOGO顯示   | ----                                                                                                                                      |
| 靜態圖片儲存   | 500                                                                                                                                       |
| 特效       | FTB, Cut, 32 Wipe with border                                                                                                             |
| 過場預覽     | Full transitions preview                                                                                                                  |
| 同步訊號輸入/出 | Built-in Genlock (internal)                                                                                                               |
| Tally輸出  | 1x D-sub 15pin, dual color                                                                                                                |
| 電腦控制     | Ethernet (free Window software)<br>RS-422/ RS-232                                                                                         |
| 攝影機控制    |                                                                                                                                           |
| 混音器      | ----                                                                                                                                      |
| 影片儲存     |                                                                                                                                           |
| 錄影檔案系統   |                                                                                                                                           |
| 錄影檔案格式   |                                                                                                                                           |
| 影像編碼     |                                                                                                                                           |
| 聲音編碼     |                                                                                                                                           |
| 直播編碼通訊協議 |                                                                                                                                           |
| 韌體更新     |                                                                                                                                           |
| 特別功能     | Motion JPEG Multi-view streaming<br>(120 memory preset, BGD Transition on/off option)<br>Free Virtual Set and Stinger transition included |
| 外型       | 1RU rack-mount mainframe                                                                                                                  |

|      |                                                                                                                                                                                                                                             |
|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 尺寸   | 440 x 215 x 49 mm (SE-1200MU)<br>430 x 261 x 70 mm (RMC-260)                                                                                                                                                                                |
| 重量   | 1.5 kg (SE-1200MU)<br>1.3 kg (RMC-260)                                                                                                                                                                                                      |
| 電源   | DC 12V, 19W (SE-1200MU)<br>DC 12V, 0.5A (RMC-260)                                                                                                                                                                                           |
| 操作溫度 | 0~40 °C                                                                                                                                                                                                                                     |
| 附件   | SE-1200MU:<br>1 x SE-1200MU product<br>1 x AD Switch DC 12V<br>1 x DB9P TO DB9P Cable<br>2 x 1U Rack Mount Ear<br>6 x M4 Screws for Rack Mount Ear<br><br>RMC-260:<br>1 x RMC-260 product<br>1 x AD Switch DC 12V<br>1 x DB9P TO DB9P Cable |