

# Datavideo Product Compare

<https://datavideo.com/in/>

|                            |  |
|----------------------------|--|
| Model Number               | <b>HS-2800</b>   |
| Product                    | <b>HD/SD 8/12-Channel Portable Video Studio</b>  |
| Video Standard             | HD & SD  |
| Video Format               | 1080i 50/59.94/60Hz<br>576i 50Hz<br>480i 59.94Hz   |
| Input Rutable / Crosspoint | Fixed  |
| Video Input                | Standard:<br>8x SDI, 2x HDMI<br>Max:<br>12x SDI, 3x HDMI                                   |
| Computer Graphic Interface | Max 3 via HDMI   |
| Down-converted Output      | 2x SDI   |
| Video Output               | 2x SDI assignable:<br>PGM, PVW, AUX & Clean Out<br>1x HDMI assignable:<br>PGM & multi-view |
| Analogue Audio Input       | 4x Balanced XLR  |

|                                |   |
|--------------------------------|---|
| Analogue Audio Output          | 2x Balanced XLR                                     |
| Digital Embedded Audio Support | Input up to 16 channels,<br>Output 4 channels       |
| Audio Delay Calibration        | Up to 8 frames                                      |
| A+V Switching                  | Yes   |
| USK                            | ----  |
| DSK                            | 2x DSK support Lumakey & Linear key<br>(Key / Fill) |
| Picture in Picture             | 2   |
| Logo Insertion                 | 2 (or 1 logo + 1 clock)                             |
| Title Creator                  |   |
| Built-in Audio Mixer           | ----  |
| Built-in Monitor Display       |   |
| Built-in Intercom & Tally      | 8 channels (4 belt-packs incl.)                     |
| <b>Streaming</b>               |   |
| Streaming                      | ----  |
| Streaming Audio Encode         | ----  |
| Streaming Protocol             | ----  |

|                                       |   |
|---------------------------------------|---|
| Streaming Control                     | ----  |
| Recording File System                 | ----  |
| Recording File Format                 | ----  |
| Streaming & Recording Setting Control | ----  |
| <b>Others</b>                         |   |
| Special Features                      | ----  |
| Dimension (LxWxH)                     | 455 x 355 x 134 mm  |
| Weight                                | 18.7 Lbs (8.5 kg), Reinforce Plastic Case   |
| Power                                 | DC 12V, 6A  |
| Operating Temp. Range                 | 0~40 °C   |
| What's in the Box                     | 1 x HS-2800 Unit<br>1 x AD Switch DC 12V with AC Cord<br>1 x CB-41 / XLR to XLR Cable<br>4 x CB-3 / XLR cable<br>1 x Goose neck MIC<br>4 x Headphone Microphone<br>4 x ITC-100SL<br>1 x Tally light<br>4 x Velcro |