

포터블 비디오 스튜디오

HD 8채널 HD 포터블 비디오 스트리밍 스튜디오

HS-2600

Video Standard	HD
Video Format	1080p 50/ 59.94/ 60Hz 1080i 50/ 59.94/ 60Hz 720p 50/ 59.94/ 60Hz
Input Routable / Crosspoint	All 8, repeatable
Video Input	4 x 3G-SDI 4 x HDMI
Computer Graphic Interface	4 via HDMI
Down-converted Output	----
Video Output	3 x 3G-SDI for PGM (AUX assignable) 1 x HDMI 1.4 for PGM (AUX assignable) 3 x HDMI 1.4 for PGM
Analogue Audio Input	2 x XLR/MIC (6.3mm) Combo Socket 1 x stereo RCA audio
Analogue Audio Output	1 x stereo RCA audio
Digital Embedded Audio Support	SDI Input/Output 4 channels, HDMI Input/Output 2 channels
Audio Delay Calibration	Up to 16 frames
A+V Switching	Yes
USK	4
DSK	2
Picture in Picture	4
Logo Insertion	2
Title Creator	Yes
Built-in Audio Mixer	----
Built-in Monitor Display	17.3" HD TFT LED backlit, 1920x1080 pix
Built-in Intercom & Tally	----

Streaming

Streaming	H.264: MAX RES 1080p H.265: MAX RES 1080p
Streaming Audio Encode	AAC 2CH, 16bit 48KHz 192Kbps
Streaming Protocol	RTSP RTMP SRT
Streaming Control	Web browser UI for configuration and control Socket commands
Recording File System	FAT32, exFAT

Recording File Format	MP4 (H.265+ AAC) or (H.264+ AAC)
Streaming & Recording Setting Control	Web UI for system configuration and control

Others

Special Features	4 Chroma-Key Virtual Studio 9 stinger transition and 4 user preset Built-in CG title overlay system Streaming encoder and recorder
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	8.5 kg, Reinforce Plastic Case
Power	DC 12V, 11A
Operating Temp. Range	0~40 °C
What's in the Box	1 x HS-2600 Unit 1 x AD Switch DC 12V with AC Cord