

포터블 비디오 스튜디오

HD 12채널 HD 포터블 비디오 스트리밍 스튜디오

HS-3200

| | |
|--------------------------------|---|
| Video Standard | Full HD |
| Video Format | 1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz |
| Input Routable / Crosspoint | All 12, repeatable |
| Video Input | 8x SDI, 4x HDMI |
| Computer Graphic Interface | 4 via HDMI |
| Down-converted Output | 1x SDI |
| Video Output | 5x SDI, 1x HDMI assignable: Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12, STILL 1, STILL 2, Flex source 3x HDMI PGM only |
| Analogue Audio Input | 4x Balanced XLR |
| Analogue Audio Output | 2x Balanced XLR |
| Digital Embedded Audio Support | Input 2 channels, Output 4 channels |
| Audio Delay Calibration | Up to 16 frames |
| A+V Switching | Yes |
| USK | 4 |
| DSK | 2, support Luma-key & Linear key (Key / Fill) |
| Picture in Picture | 8 (4x Keyer, 4x Flex Source) |
| Logo Insertion | 2 |
| Title Creator | Yes, free software download |
| Built-in Audio Mixer | ---- |
| Built-in Monitor Display | 17.3" HD TFT LED backlit, 1920x1080 pix |
| Built-in Intercom & Tally | ---- |

Streaming

| | |
|------------------------|---|
| Streaming | H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps |
| Streaming Audio Encode | AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit |
| Streaming Protocol | TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS SRT |

| | |
|---------------------------------------|--|
| Streaming Control | Web browser UI for configuration and control Socket commands |
| Recording File System | FAT, exFAT, NTFS |
| Recording File Format | MP4 |
| Streaming & Recording Setting Control | Web UI for system configuration and control |

Others

| | |
|-----------------------|--|
| Special Features | 4 Chroma-Key Virtual Studio 9 stinger transition and 4 user preset Built in TC-200 CG interface Streaming encoder and recorder 12x9 matrix seamless switch |
| Dimension (LxWxH) | 455 x 355 x 134 mm |
| Weight | 17.8 Lbs (8.1 kg), Reinforce Plastic Case |
| Power | DC 12V, 11A |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x HS-3200 Unit 1 x AD Switch DC 12V with AC Cord |