

Distribución de energía

**Power Center**  
**PD-2A**

|                                      |                                                                                                                |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------|
| AC Input                             | 100~240 VAC (50Hz or 60Hz)<br>AC input outlet: One AC input with Power Switch                                  |
| DC Backup Input                      | One DC 12V/32A<br>supports non-regulated DC 12V output                                                         |
| DC Output                            | 8<br>12V±5%, 3A XLR DC Female Jack x4<br>12V±5%, 5A XLR DC Female Jack x2<br>12V±5%, 10A XLR DC Female Jack x2 |
| Max. Power Rating                    | 400W                                                                                                           |
| DC Overload                          | DC overload protection, auto-recovery<br>fuses on each DC output terminal                                      |
| AC Overload                          | non-recovery fuse on the AC input outlet                                                                       |
| LED Indicator                        | 8 DC output LED indicators                                                                                     |
| Power Source Input Select<br>AUTO/AC | Selectable of Auto/AC input switch                                                                             |
| Dimension (LxWxH)                    | 484 x 217 x 49 mm                                                                                              |
| Weight                               | 4.6 kg                                                                                                         |
| Power                                | AC 100-240 VAC<br>DC 12V 400W                                                                                  |
| Operating Temp. Range                | 0~40 °C                                                                                                        |
| What's in the Box                    | 1 x PD-2A product<br>1 x AC CORD                                                                               |