Teleprompters portátiles

# Teleprónter de cámara PTZ

**TP-900**

| | |
|---|---|
| Device Used | 15" monitor with integrated dvPrompter Plus software |
| Camera-Mount Interface | Adjustable Lift |
| Smartphone / Tablet Size | N/A |
| Supported Languages | Unicode – All languages supported |
| Hood Dimension / Prompter Size | Width: 535mm<br>Height: 590mm<br>Depth: 350mm |
| LCD Native Resolution | 1024x768 |
| LCD Brightness | 350 NIT |
| Remote Control | * Monitoring and control via LAN<br>*Optional WR-500 wired hardware remote or FS-30 Foot Pedal<br>*Supports generic presentation remote controls with USB receivers |
| Weight | 10.3Kg |
| Operating Temp. Range | 0~40 °C |
| Power | 12V DC (Mains adapter supplied)<br>PoE (optional adapter required) |
| Carry Case Dimensions (excluding handle) | N/A |

| | |
|---|---|
| What's in the Box | 1 x 15” LCD Control Unit<br>1 x 12V universal Mains PSU<br>1 x USB Mouse<br>1 x 5m Ethernet Cable<br>1 x 3.5mm input adapter for WR-500 remote control<br>1 x TP-900 metal base tray with tripod plate<br>1 x 150 x 150 PTZ Scissor Lift<br>1 x Cloth Hood<br>1 x M4 CRV hex tool<br>1 x 9mm long ¼ thumb screw with red dot<br>1 x 9mm long ¼ thumb screw with washers<br>8 x M6*40mm screws<br>10 x M6*14mm screws<br>1 x 16mm long screw<br>1 x 3/8 to ¼ adapter<br>4 x 565mm Vertical extrusions<br>2 x 475mm horizontal extrusions with 90 degree joining blocks<br>2 x 325mm glass support extrusions with single end caps<br>2 x 250mm PTZ lift extrusions with both end caps<br>1 x 70/30 mirror glass<br>1 x Glass support bar<br>2 x Spare black extrusion end caps<br>2 x Spare M6*14mm screws<br>2 x 12V regulated DTap cable<br>1 x Small CRV hex tool to remove the tripod plate from item F<br>1 x Medium CRV hex tool to remove 90 degree joining blocks from item Q<br><br>*Tripod not included |