

Datavideo Product Compare

<https://datavideo.com/la/>

Número de modelo	PTR-15T
Product	Cabezal robótico pan-tilt 4K HDBaseT
Video Interface	HDMI 2.0 x 1 12G-SDI x 1 3G-SDI x 1 RJ45 x 1 (HDBaseT)
Video Output	2160p 60/59.94/50 2160p 30/29.97/25 1080p 60/59.94/50 1080p 30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50
Control Unit	RMC-180 MARK II RMC-300A RMC-300C SHOWCAST 100 VISCA Protocol Controller IP Control IR remote
Genlock	YES
Timecode	YES
Panning / Tilting Range	Pan: 340° Tilt: ±45°
Panning / Tilting Speed	Pan: 0.12~15° /Sec Tilt: 0.06~10° /Sec
Preset	Pan/Tilt position 199

Control Distance	1,200M by RS422 100M by DVIP
Control Protocol	Sony VISCA DVIP
Control Input	RS-422 HDBaseT
Maximum Load	4 KG Max
Control Output	RS-232 RS-422 IP Control BX-Lens LanC
Power Requirement	DC 14V~ 20V, 90W
Power Supply	DC 24/12V, 24 W Max
Operating Temp. Range	0~40 C°
Operating Humidity Range	10~80%
Storage Temp. Range	-10~60C°
Storage Humidity Range	5~80%
Weight	3.7 kg
Dimension (LxWxH)	241 x 191 x 300 mm

Optional accessories	ZEK-1 ZEK-2 PCB-1 WM-10 WM-11 CM-10 HBT-18
What's in the Box	PTR-15T Main Unit x 1 DC 19V power adaptor x 1 AC cord x 1 IR remote control x 1 DC with lock to D-Tap cable x 1 HDMI cable x 1 SDI cable x 1 Remote cable (2.5mm phone-jack to mini-din 8pin) x 1 1/4" screw x 2 1/4" to 3/8" screw adaptor x 1