

Robotic Pan Tilt Head

# Robotic Pan Tilt Head

## PTR-10 MARK II

|                          |                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------|
| Video Interface          | HDMI x 1<br>SDI x 1                                                                                     |
| Video Output             | 2160p 29.97/25<br>1080p 59.94/50<br>1080i 59.94/50<br>720p 59.94/50                                     |
| Control Unit             | RMC-180<br>RMC-300A<br>RMC-300C<br>ShowCast 100<br>VISCA Protocol Controller<br>IP Control<br>IR remote |
| Genlock                  | ---                                                                                                     |
| Timecode                 | ---                                                                                                     |
| Panning / Tilting Range  | Pan: 340°<br>Tilt: ±45°                                                                                 |
| Panning / Tilting Speed  | Pan: 0.12~15° /Sec<br>Tilt: 0.06~10° /Sec                                                               |
| Preset                   | Pan/Tilt position 50                                                                                    |
| Control Distance         | 1,200M by RS422<br>100M by DVIP                                                                         |
| Control Protocol         | Sony VISCA<br>DVIP                                                                                      |
| Control Input            | RS-422<br>DVIP                                                                                          |
| Maximum Load             | 4 KG Max                                                                                                |
| Control Output           | RS-232<br>RS-422<br>BX-Lens<br>LanC                                                                     |
| Power Requirement        | DC 12V~ 18V, 3A (Without Camera)<br>DC 12V~ 18V, 5A (With Camera)                                       |
| Power Supply             | DC 12/10/8.4/7.4V, 24W Max                                                                              |
| Operating Temp. Range    | 0~40 C°                                                                                                 |
| Operating Humidity Range | 10~80%                                                                                                  |
| Storage Temp. Range      | -10~60C°                                                                                                |
| Storage Humidity Range   | 5~80%                                                                                                   |
| Weight                   | 3.4 kg                                                                                                  |
| Dimension (LxWxH)        | 230 x 190 x 300 mm                                                                                      |

|                      |                                                                                                                                                                                                                                                                                    |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Optional accessories | ZEK-1<br>WM-10<br>WM-11<br>CM-10                                                                                                                                                                                                                                                   |
| What's in the Box    | PTR-10 Mark II Main Unit x 1<br>DC 12V power adaptor x 1<br>AC cord x 1<br>IR remote control x 1<br>DC with lock to D-Tap cable x 1<br>HDMI cable x 1<br>SDI cable x 1<br>Remote cable (2.5mm phone-jack to mini-din 8pin) x 1<br>1/4" screw x 2<br>1/4" to 3/8" screw adaptor x 1 |