

HDBaseT

3-Channel 4K HDBaseT Receiver**HBT-30**

| | |
|------------------------|--|
| Video/Audio Input | HDBaseT (RJ-45) x 3 |
| Video/Audio Output | HDMI 2.0 x 3 |
| Supported Video Format | 3840x2160p: 60/59.94/50/30/29.97/25/24/23.98 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50 720p: 60/59.94/50 525i: 59.94 NTSC 625i: 50 PAL |
| Video Process | 4K60 4:4:4, 8bit 4K60 4:2:2 10bit 4K60 4:2:0 10bit |
| Video bandwidth | Single-link 594MHz [18Gbps] |
| DVIP | RJ-45 x1(input) |
| RS-422/ RS-232 | RJ-45 x 3 (RS-232/RS-422) |
| Power | DC IN: DC 56V |
| PoE Output | 65W per channel |
| HDBaseT Distance | 1080p@60 up to 100M by CAT. 6A cable 4K@60 up to 100M by CAT. 6A cable |
| HDMI compliance | HDMI Deep Color & 4K@60 |
| HDCP compliance | HDCP 2.2/1.4 (Bypass) |
| Audio support | Surround Sound [up to 7.1 Channel) or Stereo Digital Audio |
| Dimension (LxWxH) | 440 x 125 x 44.5 mm |
| Weight | 1.8Kg |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x HBT-30 main unit 1 x AC cord 1 x DC 56V power adaptor |