

HDBaseT технология передачи сигналов

HDBaseT приемник**HBT-6**

Video/Audio Input	HDBaseT RJ-45 x1
Video/Audio Output	HDMI x1
Supported Video Format	3840x2160p: 30/29.97/25/24/23.98 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50, 720p: 60/59.94/50 525i59.94 NTSC, 625i50 PAL
Video Process	4K2K30 4:4:4 8bit 4K2K60 4:2:0 8bit
Video bandwidth	Single-link 340MHz [10.2Gbps]
DVIP	---
RS-422/ RS-232	YES
Power	DC IN: DC 48V
PoE Output	30W
HDBaseT Distance	1080p@60 60m (198ft) by CAT6 cable 4K2K@30 35m (114ft) by CAT6 cable
HDMI compliance	HDMI Deep Color, full 3D & 4K2K@30
HDCP compliance	HDCP 2.2/1.4
Audio support	Surround sound [up to 7.1ch) or stereo digital audio
Dimension (LxWxH)	88 x 76 x 30 mm
Weight	154 g
Operating Temp. Range	0~40 °C
What's in the Box	1 x HBT-6 main unit 1 x AC cord 1 x DC 48V power adaptor 2 x Screw