

LCD Мониторы

**Сдвоенный 10" видеомонитор****TLM-102**

Screen	Dual 10.1" LCD
Chassis	4RU Rack Mount
Resolution	1280x800
Viewing Angle	(H) +85/-85° (V) +85/-85°
Luminance/Contrast	300cd/m <sup>2</sup> 800:1
Video Inputs	2x 3G/HD/SD-SDI 2x HDMI
Loop Through	2x 3G/HD/SD-SDI 2x HDMI
Supported Input Resolutions	1080p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080i(50/59.94/60Hz), 720p(23.98/24/25/29.97/30/50/59.94/60Hz), 480i(NTSC), 576i(PAL)
Aspect Ratio	16:9, 4:3
Aspect Marker	YES
Safty Marker	YES
Tally LED	Live (Red) Cued (Green)
Audio In/Out	Embedded Audio on SDI and HDMI Headphone Jack
Special Features	time code, waveform, vector scope & audio level meter , peaking, zoom, pix to pix, underscan, SDI, HDMI cross conversion
Dimension (WxHxD)	482 x 178 x 38 mm
Weight	3.6 kg
Operating Temp. Range	0~40 °C
Power	DC 12V, 28W
What's in the Box	1 x TLM-102 product 1 x AD Switch DC 12V with AC Cord 1 x Tally Convertor 2 x Screw $\phi$ 3.0*6m/m 4 x Screw M5 x 10mm