

Datavideo Product Compare

<https://datavideo.com/ru/>

Номер модели	NDI Connect 100
Product	Мост NDI в UVC
Audio/Video Input	Audio Input Streaming Input (AAC/G.711A) Video Input NDI HX3 NDI HX2 RTSP RTMP(S) HLS UDP
Audio Output	HDMI Embedded Audio (2ch) UVC+UAC Audio (PCM)
Video Output	HDMI 2.0 USB-C (UVC/UAC)
Network Feature	1x RJ-45 Female (10/100/1000M Ethernet) DHCP/Static IP
Supported Video Resolution	3840×2160p@60/50/30/25/24 1920×1080p@60/50/30/25/24 1280×720p@60/50 1280×1024p@60 1280×960p@60 1024×768p@60 800×600p@60 640×480p@60 720×480p@60 720×576p@50

Supported Decoding Resolution	Up to 2160p60/50
Control	Web browser UI for configuration
Update	Via Web UI
Power	DC 12V (7~15V) Poe (IEEE 802.3at)
Environmental Conditions	Operating temperature: 0~40°C Storage temperature: -20~60°C
Dimension (LxWxH)	108mm x 101mm x 26mm
Weight	264g
Power	DC 12V/0.5A (4W)
What's in the Box	1 x NDI Connect100 1 x Power Adaptor 1 x USB-C cable