

Mobile Cast

SD 8 - Channel Mobile Video Studio

HS-600

Video Standard	SD only
Video Format	NTSC, PAL
Input Routable / Crosspoint	All 8, repeatable
Video Input	6x CV 1x DVI-D 1x DVI-I (VGA, need cable adapter)
Computer Graphic Interface	Max 2 via DVI-D, HDMI or VGA (need cable adapter for HDMI & VGA)
Down-converted Output	----
Video Output	2xCV: PGM 2xCV: AUX 1 2xCV: AUX 2 1xDVI-D: multi-view Option: 2x DV & 2x SDI
Analogue Audio Input	2x Balanced XLR (Line / Mic) 2x Unbalanced RCA (Stereo pair)
Analogue Audio Output	2x Balanced XLR 2x Unbalanced RCA (Stereo pair)
Digital Embedded Audio Support	Output only (optional DV & SDI)
Audio Delay Calibration	Up to 700ms or 17 frames
A+V Switching	Yes
USK	----
DSK	1x Lumakey
Picture in Picture	2
Logo Insertion	2
Title Creator	----
Built-in Audio Mixer	Yes, 3 channels
Built-in Intercom & Tally	8 channels (4 belt-packs incl.)

Streaming

Streaming	----
Streaming Audio Encode	----
Streaming Protocol	----
Streaming Control	----
Recording File System	----
Recording File Format	----

Streaming & Recording Setting Control	----
--	------

Others

Special Features	----
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	19.6 Lbs (9 kg), Reinforce Plastic Case
Power	DC 12V, 5A
Operating Temp. Range	0~40 °C
What's in the Box	----