

影像格式轉換器

HD/SD影像格式轉換器**DAC-70**

| | |
|-----------------|--|
| 轉換功能 | VGA/HDMI/SDI to HDMI/SDI Multi-format Up/Down/Cross |
| 影像輸入 | 1x VGA, 1x HDMI, 1x 3G/HD/SD-SDI (support Level A and Level B) |
| 回路輸出 | Yes |
| 影像輸出 | 2x 3G/HD/SD-SDI with embedded Audio (support Level A and Level B) 1x HDMI |
| 聲音輸入 | 2x RCA (Stereo Pair), 2x SDI/HDMI Audio embedded |
| 聲音輸出 | SDI embedded audio up to 8CH, 48KHz, PCM audio HDMI embedded audio up to 8CH, 48KHz, PCM audio |
| 聲音格式選擇 | ---- |
| 聲音增益 | ---- |
| 影像格式 | 1080p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080psf(23.98/24/25/29.97/30Hz), 1080i (50/59.94/60Hz), 720p (50/59.94/60Hz), 625i, 576p, 576i, 525i, 480p, 480i, 1920x1080(60Hz), 1280x720(60Hz), 1600x1200(60Hz), 1400x1050(60Hz), 1366x768(60Hz), 1280x1024(60Hz), 1024x768(60Hz), 800x600 (60Hz) |
| 輸出解析度 | 1080p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080i (50/59.94/60Hz), 720p (50/59.94/60Hz), 625i, 525i |
| 等化器 | Yes |
| 重新鎖定 | Yes |
| SDI Cable Drive | Yes |
| | Mini USB x 1 |
| 尺寸 | 112 x 85 x 45 mm |
| 重量 | 0.4 kg |
| 操作溫度 | 0~40 °C |
| 電源 | DC 12V, 6W |
| 附件 | 1 x DAC-70 1 x AD Switch DC 12V 1 x DIP switch Pin 8 label |