

網路直播解碼器

# HDMI 網路直播解碼器

## NVD-30 MARK II

|         |                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 聲音/影像輸入 | Stream Input <ul style="list-style-type: none"><li>· RTSP over UDP (Unicast / Multicast)</li><li>· RTSP over TCP</li><li>· RTSP over HTTP</li><li>· SRT (Secure Reliable Transport) caller</li><li>· MPEG-TS over UDP</li><li>· RTMP Pull</li><li>· RTMP Push (Internal Server)</li><li>· UDP raw (Unicast/Multicast)</li><li>· HLS over HTTP</li><li>· MPEG-TS over TCP Pull</li><li>· Video sharing websites</li></ul> |
| 聲音輸出    | 2 x RCA(L/R)<br>HDMI embedded audio                                                                                                                                                                                                                                                                                                                                                                                      |
| 影像輸出    | Composite (analogue)<br>HDMI (digital)                                                                                                                                                                                                                                                                                                                                                                                   |
| 網路功能    | 1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP                                                                                                                                                                                                                                                                                                                                                                        |
| 支持影像格式  | 1080p 60/59.94/30/29.97/25/24<br>1080i 60/59.94/50<br>720p 60/59.94/50<br>576i 50 (PAL)<br>480i 60 (NTSC)                                                                                                                                                                                                                                                                                                                |
| 支持解碼格式  | Up to 1080p60/50                                                                                                                                                                                                                                                                                                                                                                                                         |
| 控制      | Web browser UI for configuration and control.<br>TCP/IP Socket commands                                                                                                                                                                                                                                                                                                                                                  |
| 更新      | Automatic firmware upgrade                                                                                                                                                                                                                                                                                                                                                                                               |
| 工作電源    | Input AC 100~240V Switching Adaptor<br>Output DC 12V / 0.5 A                                                                                                                                                                                                                                                                                                                                                             |
| 環境條件    | Operating temperature: 0~40°C, Storage temperature: -10~60°C                                                                                                                                                                                                                                                                                                                                                             |
| 尺寸      | 220 x 143 x 47 mm                                                                                                                                                                                                                                                                                                                                                                                                        |
| 重量      | 1 kg                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 電源      | DC 12V, 0.5A                                                                                                                                                                                                                                                                                                                                                                                                             |
| 附件      | 1 x NVD-30 MARK II product<br>1 x AD Switch DC 12V<br>1 x Remote Control                                                                                                                                                                                                                                                                                                                                                 |