

Datavideo Product Compare

<https://datavideo.com/tw/>

型號	HS-1300
產品	HD 6通道手提式移動錄播導播室
影像系統	HD
影像格式	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
輸入格式設定	All 6, repeatable
影像輸入	4x HD-SDI 2x HDMI
電腦輸入	2 via HDMI
下變換轉換器	----
影像輸出	3x HDMI + 2x SDI assignable: AUX 1-6, PGM, PVW, PGM Clean or Multiview
聲音輸入	2x Balanced XLR
聲音輸出	1x Stereo headphone
聲音嵌入	Input 2 channels, Output 2 channels
聲音延遲	----
聲音同步切換	Yes
USK	2x USK support Chromakey
DSK	2, support Lumakey & Linear key (Key / Fill)
子母畫面	1
LOGO	----
字幕機	----

混音機	----
監看螢幕	17.3" HD TFT LED backlit, 1600x900 pix
通話系統	----
Streaming	
串流影片編碼	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
串流聲音編碼	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
串流協議	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish) HLS SRT
串流控制	Web browser UI for configuration and control Socket commands
錄製檔案系統	FAT, exFAT, NTFS
錄製檔案格式	MP4
錄製設定控制	Web UI for system configuration and control
Others	
特別功能	Streaming encoder and recorder 2 chromakey virtual studio 9 stinger transition and 30 virtual sets included
尺寸	455 x 355 x 134 mm
重量	16.3 Lbs (7.4 kg), Reinforce Plastic Case
电源	DC 12V, 5A
操作溫度	0~40 °C
附件	1 x HS-1300 Product 1 x AD Switch DC 12V with AC Cord

