HDBaseT

# 4-Channel HDBaseT Receiver with SDI and HDMI Outputs

**HBT-50**

| | |
|---|---|
| Video/Audio Input | HDBaseT x 4 (with PoE and IEEE 802.3at)<br>Cable Type: Cat6A shielded |
| Video/Audio Output | HDMI x 4 (up to 1080p50/59.94/60)<br>SDI x 4 (up to 1080p50/59.94/60) |
| Supported Video Format | 1080p: 60/59.94/50/30/29.97/25/24/23.98<br>1080i: 60/59.94/50, 720p: 60/59.94/50 |
| Video Process | --- |
| Video bandwidth | --- |
| DVIP | RJ-45 x1(input) |
| RS-422/ RS-232 | RJ-45 x 4 (RS-232/RS-422) |
| Power | AC In |
| PoE Output | 65W per channel |
| HDBaseT Distance | 1080p50/59.94/60 up to 100m by CAT.6 cables |
| HDMI compliance | --- |
| HDCP compliance | --- |
| Audio support | --- |
| Dimension (LxWxH) | 440 x 286 x 49mm |
| Weight | 4.2 kg |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x HBT-50 main unit<br>1 x AC Cord |