

Video Decoder

HDMI IP Video Decoder**NVD-30 MARK II**

| | |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Audio/Video Input | <p>Stream Input</p> <ul style="list-style-type: none"> · RTSP over UDP (Unicast / Multicast) · RTSP over TCP · RTSP over HTTP · SRT (Secure Reliable Transport) caller · MPEG-TS over UDP · RTMP Pull · RTMP Push (Internal Server) · UDP raw (Unicast/Multicast) · HLS over HTTP · MPEG-TS over TCP Pull · Video sharing websites |
| Audio Output | <p>2 x RCA(L/R) HDMI embedded audio</p> |
| Video Output | <p>Composite (analogue) HDMI (digital)</p> |
| Network Feature | <p>1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP</p> |
| Supported Video Resolution | <p>1080p 60/59.94/30/29.97/25/24 1080i 60/59.94/50 720p 60/59.94/50 576i 50 (PAL) 480i 60 (NTSC)</p> |
| Supported Decoding Resolution | <p>Up to 1080p60/50</p> |
| Control | <p>Web browser UI for configuration and control. TCP/IP Socket commands</p> |
| Update | <p>Automatic firmware upgrade</p> |
| Power | <p>Input AC 100~240V Switching Adaptor Output DC 12V / 0.5 A</p> |
| Environmental Conditions | <p>Operating temperature: 0~40°C, Storage temperature: -10~60°C</p> |
| Dimension (LxWxH) | <p>220 x 143 x 47 mm</p> |
| Weight | <p>1 kg</p> |
| Power | <p>DC 12V, 0.5A</p> |
| What's in the Box | <p>1 x NVD-30 MARK II product 1 x AD Switch DC 12V 1 x Remote Control</p> |