

Datavideo Product Compare

<https://datavideo.com/us/>

Model Number	HBT-30
Product	3-Channel HDBaseT Receiver with HDMI Outputs
Video/Audio Input	HDBaseT (RJ-45) x 3 Cable Type: Cat6A shielded
Video/Audio Output	HDMI 2.0 x 3
Supported Video Format	3840x2160p: 60/59.94/50/30/29.97/25/24/23.98 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50 720p: 60/59.94/50 525i: 59.94 NTSC 625i: 50 PAL
Video Process	4K60 4:4:4, 8bit 4K60 4:2:2 10bit 4K60 4:2:0 10bit
Video bandwidth	Single-link 594MHz [18Gbps]
DVIP	RJ-45 x1(input)
RS-422/ RS-232	RJ-45 x 3 (RS-232/RS-422)
Power	DC IN: DC 56V
PoE Output	65W per channel
HDBaseT Distance	1080p@60 up to 100M by CAT. 6A cable 4K@60 up to 100M by CAT. 6A cable
HDMI compliance	HDMI Deep Color & 4K@60

HDCP compliance	HDCP 2.2/1.4 (Bypass)
Audio support	Surround Sound [up to 7.1 Channel) or Stereo Digital Audio
Dimension (LxWxH)	440 x 125 x 44.5 mm
Weight	1.8Kg
Operating Temp. Range	0~40 °C
What's in the Box	1 x HBT-30 main unit 1 x AC cord 1 x DC 56V power adaptor