

# Datavideo Product Compare

<https://datavideo.com/us/>

|                            |                                                                                                                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model Number               | <b>PTC-325</b>                                                                                                                                                                                                                    |
| Product                    | <b>4K 30x Tracking PTZ Camera</b>                                                                                                                                                                                                 |
| Video format/Resolution    | HDMI:<br>2160p60/59.94/50/30/29.97/25<br>1080p60/59.94/50/30/29.97/25<br>1080i60/59.94/50<br>720p60/59.94/50<br>*2160p60/59.94/50 YUV 4:2:2<br><br>SDI:<br>1080p 60/59.94/50/30/29.97/25<br>1080i 60/59.94/50<br>720p 60/59.94/50 |
| Image Sensor               | Sony 1/2.8" CMOS                                                                                                                                                                                                                  |
| Effective Pixels (approx.) | 8.46Mega Pixels                                                                                                                                                                                                                   |
| S/N Ratio                  | ≥55dB                                                                                                                                                                                                                             |
| Min. Illumination          | 0.5 Lux @ (F1.8, AGC ON)                                                                                                                                                                                                          |
| Electronic Shutter         | 1/30s ~ 1/10000s                                                                                                                                                                                                                  |
| Zoom Ratio                 | 30x Optical, 16x Digital Zoom                                                                                                                                                                                                     |
| Effective Zoom Ratio       | 30x                                                                                                                                                                                                                               |

|                                  |                                                 |
|----------------------------------|-------------------------------------------------|
| Gamma Control                    | N/A                                             |
| Iris Control                     | Auto / Manual                                   |
| Digital Noise Reductions         | 3D                                              |
| On-Screen Display (OSD)          | English/Simplified Chinese/Traditional Chinese  |
| White Balance                    | Auto, Indoor, Outdoor, OnePush, Manual, VAR     |
| AGC / Gain Control               | Yes                                             |
| HDR/WDR                          | N/A                                             |
| Mirror / Flip Image              | Yes                                             |
| Focus Mode                       | Auto/Manual                                     |
| Panning / Tilting Range          | Pan: 300°<br>Tilt: +90° to -15°                 |
| Panning / Tilting Speed          | Pan: 0.876°/s~43°/s<br>Tilt: 0.693°/s ~21.32°/s |
| Preset                           | 255                                             |
| Focal Length                     | 30x, f = 4.5mm ~135mm, F1.8 ~ F4.7              |
| Field of View (Horizontal, Wide) | 62.3°                                           |
| Image Compensation               | Back light compensation                         |

|                                   |                                                                                 |
|-----------------------------------|---------------------------------------------------------------------------------|
| Video Output                      | HDMI 2.0 x1<br>3G-SDI x1<br>10/100/1000M RJ45 (PoE) x1                          |
| Audio Input                       | 3.5 mm x1 (mic in/line in)<br>switch from Web UI                                |
| Tally LED                         | Yes                                                                             |
| Lens Filter                       | N/A                                                                             |
| Control Protocol                  | Pelco-D, Pelco-P,<br>VISCA, VISCA over IP,<br>DVIP, ONVIF, NDI                  |
| Remote Control Interface          | IR<br>Web GUI<br>RS-422/RS-232<br>DVIP<br>NDI                                   |
| Video Compression Format          | H.264/H.265/MJPEG                                                               |
| Audio Compression Format          | AAC, G711                                                                       |
| Audio Bitrate                     | 96Kbps, 128Kbps,256Kbps                                                         |
| HD IP Interface                   | ----                                                                            |
| Streaming Protocols               | RTSP, RTMP(S), ONVIF, Multicast, SRT, NDI Hx3 (1080p)                           |
| First Stream Supported Resolution | 3840x2160<br>1920x1080<br>1280x720<br>1024x576<br>960x540<br>640x480<br>640x360 |

|                                    |                                                                     |
|------------------------------------|---------------------------------------------------------------------|
| Second Stream Supported Resolution | 720x480<br>640x360<br>480x270<br>320x240                            |
| Video Bitrate                      | 32Kbps ~ 50Mbps (Single Stream)                                     |
| Video Bitrate Mode                 | VBR, CBR                                                            |
| Encoding Frame rate                | 50Hz: 1-50fps<br>60Hz: 1-60fps                                      |
| POE                                | IEEE 802.3at<br>PoE+                                                |
| F/W Update                         | Via Web UI or USB 2.0                                               |
| IR Control                         | Yes                                                                 |
| Camera Control Unit                | RMC-2P<br>RMC-180 series/<br>RMC-300 series/<br>PTZ View Assist APP |
| Tripod Mount                       | 1/4-20 UNC                                                          |
| Optional Accessories               | WM-1/ WM-10/ WM-11                                                  |
| Color                              | Black/White                                                         |
| Dimension (LxWxH)                  | 173 (W) x 219 (H) x 189.08 (D)                                      |
| Weight                             | 2.6 kg                                                              |
| Operating Temp. Range              | 0~40 °C                                                             |
| Power                              | DC 12V 21W                                                          |

What's in  
the Box

- 1 x PTC-325 product
- 1 x IR remote controller
- 1 x Ceiling mount bracket-A
- 1 x Ceiling mount bracket -B
- 6 x Ceiling mount bracket screw M3\*4mm
- 1 x DC 12V Power Adaptor
- 1 x Safety cable